# ALTV615DC44ULM, ALTV615DC44UCBM
# UL Listed DC CCTV Power Supply

Rev. DSALTV615DC44ULM - B23F

## Overview

- These Altronix DC Wall Mount CCTV Power Supplies provide 6VDC to 15VDC distributed via four (4) Class 2 Rated fuse or PTC protected power limited outputs for powering CCTV Cameras, heaters and other video accessories.

### ALTV615DC44ULM

- Four (4) Class 2 Rated fused protected power limited outputs.
- Outputs are rated @ 3.5 amp.

### ALTV615DC44ULM3

- ALTV615DC44ULM w/factory installed 3-wire line cord.

### ALTV615DC44UCBM

- Four (4) Class 2 Rated PTC protected power limited outputs.
- Outputs are rated @ 2.5 amp.

### ALTV615DC44UCBM3

- ALTV615DC44UCBM w/factory installed 3-wire line cord.

## Specifications

- Input 115VAC 50/60Hz, .9 amp.
- 6VDC to 15VDC adjustable @ 4 amp total supply current.
- Filtered and electronically regulated outputs.
- Short circuit and thermal overload protection.
- Power ON/OFF switch.
- AC and DC power LEDs.
- Spare fuses provided (on fuse protected models).
- Unit maintains camera synchronization.
- Ease of installation saves time and eliminates costly labor.
- Product weight:
  - ALTV615DC44ULM: 7.4 lbs.
  - ALTV615DC44ULM3: 7.7 lbs.
  - ALTV615DC44UCBM: 7.4 lbs.
  - ALTV615DC44UCBM3: 7.7 lbs.
- Shipping weight:
  - ALTV615DC44ULM: 8.0 lbs.
  - ALTV615DC44ULM3: 8.3 lbs.
  - ALTV615DC44UCBM: 8.0 lbs.
  - ALTV615DC44UCBM3: 8.3 lbs.

## Agency Approvals

UL Listed for Commercial CCTV Equipment (UL 2044).

CUL Listed - CSA Standard C22.2 No.1-98, Audio, Video and Similar Equipment.

# ***Enclosure Dimensions***

8.5"H x 7.5"W x 3.5"D